

Generated Documentation



Contents

Package default Classes	1
Class Atom	1
Var \$atom_archive	1
Var \$atom_author	1
Var \$atom_code_page	1
Var \$atom_content	1
Var \$atom_home	1
Var \$atom_id	1
Var \$atom_idtag	1
Var \$atom_language	1
Var \$atom_last_modified	2
Var \$atom_mysql_body	2
Var \$atom_mysql_link	2
Var \$atom_mysql_published	2
Var \$atom_mysql_table	2
Var \$atom_mysql_title	2
Var \$atom_mysql_updated	2
Var \$atom_output	2
Var \$atom_time_zone	2
Var \$atom_title	2
Var \$atom_version	2
Var \$atom_xsl	2
Constructor Atom	2
Method body	3
Method create_file_output	3
Method create_screen_output	3
Method footer	3
Method header	3
Method mysql_connect	4
Method mysql_query	4
Method set_archive	4
Method set_author	4
Method set_code_page	5
Method set_home	5
Method set_id	5
Method set_idtag	5
Method set_language	5
Method set_mysql	6
Method set_output	6
Method set_time_zone	6
Method set_title	6
Method set_xsl	7
Method Atom	7

Appendices	8
Appendix A - Class Trees	9
default	9

Package default Classes

Class Atom *[line 25]*

- **Package** default

Atom::\$atom_archive

mixed = [line 38]

Atom::\$atom_author

mixed = [line 40]

Atom::\$atom_code_page

mixed = [line 33]

Atom::\$atom_content

mixed = [line 45]

Atom::\$atom_home

mixed = [line 42]

Atom::\$atom_id

mixed = [line 36]

Atom::\$atom_idtag

mixed = [line 41]

Atom::\$atom_language

mixed = [line 34]

Atom::\$atom_last_modified

mixed = [line 39]

Atom::\$atom_mysql_body

mixed = [line 29]

Atom::\$atom_mysql_link

mixed = [line 26]

Atom::\$atom_mysql_published

mixed = [line 30]

Atom::\$atom_mysql_table

mixed = [line 27]

Atom::\$atom_mysql_title

mixed = [line 28]

Atom::\$atom_mysql_updated

mixed = [line 31]

Atom::\$atom_output

mixed = [line 44]

Atom::\$atom_time_zone

mixed = [line 32]

Atom::\$atom_title

mixed = [line 37]

Atom::\$atom_version

mixed = [line 35]

Atom::\$atom_xsl

mixed = [line 43]

Constructor *null* function Atom::Atom([\$version = "v0.3"]) *[line 55]*

Function Parameters:

- *version* **\$version** Version of Atom feed.

Constructor Create an Atom object.

nothing function Atom::body(0) [*line 361*]

Function Parameters:

- *null 0*

Create Atom feed body.

nothing function Atom::create_file_output(0) [*line 231*]

Function Parameters:

- *null 0*

Make Atom feed output to file.

TODO: File exist check, setting permissions, ...

nothing function Atom::create_screen_output(0) [*line 245*]

Function Parameters:

- *null 0*

Make Atom feed output to browser.

nothing function Atom::footer(0) [*line 350*]

Function Parameters:

- *null 0*

Create Atom feed footer.

nothing function Atom::header(0) [*line 305*]

Function Parameters:

- *null 0*

Create Atom feed header accord version.

nothing function Atom::mysql_connect(\$db_conn) [*line 262*]

Function Parameters:

- *db_conn* **\$db_conn** Associative array of data for connection. = array(
 "username" => "", "password" =>
 "", "hostname" => "",
 "dbname" => "");

Connect to MySQL server and set character coding to LATIN2

result function Atom::mysql_query(\$stmt) [*line 288*]

Function Parameters:

- *stmt* **\$stmt** MySQL query.

Create MySQL query.

nothing function Atom::set_archive(\$url) [*line 157*]

Function Parameters:

- *url* **\$url** Location of data included in feed.

Set Atom feed data archive location. Etc.

News archive or news history.

nothing function Atom::set_author(\$author) [*line 169*]

Function Parameters:

- *author* **\$author** Author name.

Set Atom feed owner - author.

nothing function Atom::set_code_page(\$code_page) [*line 133*]

Function Parameters:

- *code_page* **\$code_page** Code page - example: iso-8859-2

Set Atom feed document code page

nothing function Atom::set_home(\$url) [*line 193*]

Function Parameters:

- *url* **\$url** Atom feed data home.

Set Atom feed data home - server.

nothing function Atom::set_id(\$id) [*line 97*]

Function Parameters:

- *id* **\$id** Atom feed identification.

Set Atom feed identification

nothing function Atom::set_idtag(\$id) [*line 181*]

Function Parameters:

- *id* **\$id** Identification tag.

Set Atom feed identification tag for items.

nothing function Atom::set_language(\$language) [*line 145*]

Function Parameters:

- *language* **\$language** Language - example: cs-cz

Set Atom feed document language

nothing function Atom::set_mysql(\$table_name, \$title_column, \$body_column, \$published_column, \$updated_column) [*line 81*]

Function Parameters:

- *table_name* **\$table_name** Atom feed data table name.
- *title_column* **\$title_column** Atom feed title column name.
- *body_column* **\$body_column** Atom feed body column name.
- *published_column* **\$published_column** Atom feed published date column name.
- *updated_column* **\$updated_column** Atom feed updated date column name.

Set Atom feed MySQL properties.

nothing function Atom::set_output(\$filepath) [*line 217*]

Function Parameters:

- *filepath* **\$filepath** Atom feed data output filename.

Set Atom feed data output file.

nothing function Atom::set_time_zone(\$time_zone) [*line 121*]

Function Parameters:

- *time_zone* **\$time_zone** Time zone - example: +01:00

Set Atom feed time zone

nothing function Atom::set_title(\$title) [*line 109*]

Function Parameters:

- *title* **\$title** Atom feed title.

Set Atom feed title

nothing function Atom::set_xsl(\$xsl) [*line 205*]

Function Parameters:

- *xs/ \$xsl* Path to XSL style file.

Set Atom feed data XSL style file.

nothing function Atom::_Atom(0) [*line 409*]

Function Parameters:

- *null 0*

Descruction of Atom feed

Appendices

Appendix A - Class Trees

Package default

Atom

- [Atom](#)

Index

A

Atom	1
Atom::\$atom_archive	1
Atom::\$atom_author	1
Atom::\$atom_code_page	1
Atom::\$atom_content	1
Atom::\$atom_home	1
Atom::\$atom_id	1
Atom::\$atom_idtag	1
Atom::\$atom_language	1
Atom::\$atom_last_modified	2
Atom::\$atom_mysql_body	2
Atom::\$atom_mysql_link	2
Atom::\$atom_mysql_published	2
Atom::\$atom_mysql_table	2
Atom::\$atom_mysql_title	2
Atom::\$atom_mysql_updated	2
Atom::\$atom_output	2
Atom::\$atom_time_zone	2
Atom::\$atom_title	2
Atom::\$atom_version	2
Atom::\$atom_xsl	2
Atom::body()	3
<i>Create Atom feed body.</i>	
Atom::create_file_output()	3
<i>Make Atom feed output to file.</i>	
Atom::create_screen_output()	3
<i>Make Atom feed output to browser.</i>	
Atom::footer()	3
<i>Create Atom feed footer.</i>	
Atom::header()	3
<i>Create Atom feed header accord version.</i>	
Atom::mysql_connect()	4
<i>Connect to MySQL server and set character coding to LATIN2</i>	
Atom::mysql_query()	4
<i>Create MySQL query.</i>	
Atom::set_archive()	4
<i>Set Atom feed data archive location. Etc.</i>	
Atom::set_author()	4
<i>Set Atom feed owner - author.</i>	
Atom::set_code_page()	5
<i>Set Atom feed document code page</i>	
Atom::set_home()	5
<i>Set Atom feed data home - server.</i>	
Atom::set_id()	5

<i>Set Atom feed identification</i>	
Atom::set_idtag()	5
<i>Set Atom feed identification tag for items.</i>	
Atom::set_language()	5
<i>Set Atom feed document language</i>	
Atom::set_mysql()	6
<i>Set Atom feed MySQL properties.</i>	
Atom::set_output()	6
<i>Set Atom feed data output file.</i>	
Atom::set_time_zone()	6
<i>Set Atom feed time zone</i>	
Atom::set_title()	6
<i>Set Atom feed title</i>	
Atom::set_xsl()	7
<i>Set Atom feed data XSL style file.</i>	
Atom:: Atom()	7
<i>Descruction of Atom feed</i>	

C

constructor Atom::Atom()	2
<i>Constructor Create an Atom object.</i>	